




SQUBE on base

CEILING SURFACE



285 | 297




1.0 LED

LED COB 6W | phase-cut dim
220-240VAC | 50-60Hz
aluminium powder coated

IP20 0°-90° 39° SDCM3 L70|55K 0.43kg

CODE	
White	144268W_
Black	144268B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	415 >90	3
3000K	430 >90	5
1800-3000K	350 >80	9




1.1 LED

LED COB 12W | phase-cut dim
220-240VAC | 50-60Hz
aluminium powder coated

IP20 0°-90° SDCM3 L70|55K 0.44kg

CODE	
White	144468W_
Black	144468B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K 32°	940 >90	3
3000K 32°	970 >90	5
1800K-3000K 58°	640 >80	9



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

IP20 0°-90° 0.43kg

CODE	
White	144220W0
Black	144220B0

OPTIONAL

PAR16 6.5W GU10 phase-cut dim		CODE
2700K 460lm		901228W3
2700K 437lm		901228B3
3000K 500lm		901228W5
3000K 457lm		901228B5

more lamps and specs on page 743