



WEVER & DUCRÉ
LIGHTING

SQUBE

on base 1.0 PAR16

144220W0

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling , Surface
Tilt max 90°
White Matt
RAL 9003^a
IP20
Interior
Output: 505^b, 550^c lm
CIE flux code: 94 98 100 100 100

LED

Lamp PAR16
Socket GU10
max. 12.0 W
2700 K^b, 3000 K^c
CRI ≥ 90

OPTICAL

Beam angle 35°

ELECTRICAL

100 - 240 V
LED Inset 6.5 W
Class 1


PHYSICAL

Diameter 55 mm
Height 119 mm
0.43 kg


^a Color may deviate slightly due to production conditions.

^b PAR16 LAMP 2700K CRI90


^c PAR16 LAMP 3000K CRI90



Ceiling surface spotlight made from die-cast aluminium; surface White Matt; powder coated, matt texture; RAL 9003; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 90° tiltable; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION



[144220W0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

SQUBE

on base 1.0 PAR16

144220W0

CONE DIAGRAM

PAR16 LAMP 3000K 35°
CRI90

h (m)	E0° (lx)	ø (m)
1	1360	0.62
2	340	1.24
3	150	1.87
4	80	2.49
5	50	3.11

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-60	9 0 5 2 2 7 S 4