



WEVER & DUCRÉ
LIGHTING

CENO SURFACE 1.0

176664Q5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Tilt max 90°

Rotation 350°

Bronze

IP20

Interior

Output: 540 lm

CIE flux code: 99 100 100 100 100

LED

3000 K

CRI ≥ 90

2 SDCM

OPTICAL

Beam angle 31°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 8.8 W

Class 1

PHYSICAL


Diameter 34 mm

Height 55 mm

0.21 kg



Ceiling surface spotlight made from die-cast aluminium; with rectangular base; surface Bronze; wet painted, matt smooth; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; beam angle 31°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; PCI; driver included; optional honey-comb louver available, to reduce glare; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

CENO SURFACE 1.0

176664Q5

LIGHT DISTRIBUTION



CONE DIAGRAM

31°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 1550 | 0.56 |
| 2 | 390 | 1.12 |
| 3 | 170 | 1.68 |
| 4 | 100 | 2.23 |
| 5 | 60 | 2.79 |

OPTICAL

Honeycomb Louver

| TYPE | Ø (MM) | ORDERCODE |
|----------------------------------|--------|-----------------|
| CENO PIRRO BLIEK ROUND PETIT | 29 | 9 0 0 5 1 1 3 1 |