



WEVER & DUCRÉ  
LIGHTING

# RINI SNEAK 1.0 PAR16

154220B0

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling , Semi-Recessed

Black Matt

RAL 9011<sup>a</sup>

Front IP44

Back IP20

Interior

Output: 390<sup>b</sup>, 405<sup>c</sup> lm

CIE flux code: 94 98 100 100 85

## LED

Lamp PAR16

Socket GU10

max. 12.0 W

2700 K<sup>b</sup>, 3000 K<sup>c</sup>

CRI ≥ 90

L80 / 55000 h

## OPTICAL

Wide Flood , Beam angle 35°

## ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

## PHYSICAL

Diameter 84 mm

Height 99 mm

0.16 kg

wire springs

## CUTOUT

Diameter 76-79 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 25 mm

Recessed depth 80 mm


<sup>a</sup> Color may deviate slightly due to production conditions.

<sup>b</sup> PAR16 LAMP 2700K CRI90


<sup>c</sup> PAR16 LAMP 3000K CRI90



Round ceiling recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; installation without tools using wire springs; recessed depth 80 mm; suitable for ceiling thickness of 4-25 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP44; PC2; lamp not included;



## LIGHT DISTRIBUTION



[154220B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# RINI SNEAK 1.0 PAR16

154220B0

## CONE DIAGRAM

wide flood 35°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	968	0.62
2	242	1.24
3	108	1.87
4	60	2.49
5	39	3.11

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50-60	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50-60	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50-60	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50-60	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50-60	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50-60	9 0 5 2 2 7 S 4