

# Technical Data Sheet

## Line



### Product description

The use of state-of-the-art LED technology in conventional office and hall illumination provides a lot of advantages like an optimal light distribution and an increased lifetime all at an affordable price. LED Lights are fully compatible with existing conventional lighting infrastructure, and are the perfect choice for both new and replacement markets.




### Technical description

<b>Mains voltage</b>	220 - 240 V AC, 50 - 60Hz
<b>Connection</b>	3-pole
<b>Protection rating</b>	IP 20
<b>Light source</b>	LED
<b>Optical system</b>	Prismatic diffusor
<b>Wiring</b>	Fix / 1-10V / Zigbee 3.0 / DALI
<b>Diffuser material</b>	Polycarbonate
<b>Housing material</b>	Aluminum
<b>Ambient temperature</b>	0 °C to +30 °C
<b>Service lifetime (L90, B10)</b>	50 000h
<b>Warranty</b>	5 years

Version	CCT	Power consup.	Output	CRI (Ra)	lm / W
1200mm	4000 k	9,5 W	743 lm	80+	78
		19 W	1486 lm	80+	78
		38 W	2972 lm	80+	78
		54 W	4245 lm	80+	78

### Dimensions

1200



l 1200 mm  
w 50 mm  
h 70 mm

### Optics



■ 0°-180° ■ 90°-270°