



## Info generali

### Interno - Lampade da soffitto

Indoor ceiling mounted projector with integrated LED sources and direct light emission

|                      |                           |
|----------------------|---------------------------|
| <b>Ean</b>           | 8021696205991             |
| <b>Articolo</b>      | NITRO PL ROUND D08 BIANCO |
| <b>Installazione</b> | Lampade da soffitto       |
| <b>Garanzia</b>      | 5 years                   |
| <b>Peso lordo</b>    | 0.44 kg                   |
| <b>Volume</b>        | 0.00125 m <sup>3</sup>    |

## Info tecniche e installative

|                                  |  |
|----------------------------------|--|
| <b>Peso netto</b>                | 0.39 kg  |
| <b>Classe di isolamento</b>      | II   |
| <b>Grado di protezione</b>       | IP20   |
| <b>Conformità</b>                | CE   |
| <b>Temperatura d'esercizio</b>   | 0° ~ +40 °C  |
| <b>Efficienza a pieno carico</b> | X  |
| <b>Dimmer</b>                    | NO, On-Off   |
| <b>Alimentazione</b>             | 220-240 V AC 50/60 Hz  |
| <b>Alimentatore</b>              | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Info sorgente e prestazionali

|                              |   |
|------------------------------|---|
| <b>Sorgente integrata</b>    | Integrated LED module                     |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only) |
| <b>Potenza</b>               | LED 10 W                                  |
| <b>Emissione</b>             | Direct                                    |
| <b>Consumo massimo</b>       | max 10,00 W                               |
| <b>Caratteristiche LED</b>   | LED COB BRIDGELUX                         |
| <b>CCT LED</b>               | 3000 K                                    |
| <b>Durata LED (t. 25°c)</b>  | 50000 h                                   |
| <b>CRI</b>                   | > 90                                      |
| <b>Fascio luminoso</b>       | 28°                                       |
| <b>Flusso sorgente</b>       | 1100 lm                                   |
| <b>Flusso utile</b>          | 950 lm                                    |
| <b>Rischio fotobiologico</b> | 2   |
| <b>Lampadina inclusa</b>     | 1 - E14 OLIVA 4W 3000K CRI80 SATIN        |